

LUMIFIBER FIBER OPTIC SOLUTION



ODF PANEL

FEATURES

- Available in 48Port, 96Port, 120Port and 144Port
- Can load into standard 19" and 23" distribution frame
- Suitable for single and ribbon fiber
- Splice tray is included in each panel
- Front marking on the panel for ease of identification and tagging
- Rotary panel design for easy management and operation

APPLICATIONS

- Fiber Optic Telecommunication
- Optical network equipment
- CWDM (Coarse Wavelength Division Multiplex)



LM-ODFP-96

TECHNICAL CHARACTERISTIC

Parameter	Value
Material	Cold roll steel
Storage Temperature	-40°C to +70°C
Relative Humidity	≤85% (+30°C)
Colour	White (RAL7035)

ORDERING INFORMATION

PRODUCT NUMBER	Dimension (WxDxH) mm	Adapter Port	Splicing capacity
LM-ODFP-48	440 x 396 x 89 (2U)	48 SC SIMPLEX	48 fibers
LM-ODFP-96	440 x 396 x 132 (3U)	96 SC SIMPLEX	96 fibers
LM-ODFP-120	440 x 396 x 132 (3U)	120 SC SIMPLEX	120 fibers
LM-ODFP-144	440 x 396 x 170 (3U)	144 SC SIMPLEX	144 fibers