

LUMIFIBER RACKING SYSTEM



FLOOR STANDING RACK

FEATURES

- Steel frame with epoxy powder finishing
- With the option of Perspex, perforated or tempered glass door
- Removable side panels with lock
- Cable entry from top or bottom with knock out plate
- 4 adjustable panel mounting members
- 1 row of 13A Power Points
- Caster wheel
- 40 sets of M6 caged nuts



Rack Capacity / Size

Capacity (U)	Height (mm)	Width (mm)	Depth (mm)
15U	937	600/800/1000	800/900/1000
18U	970	600/800/1000	800/900/1000
24U	1237	600/800/1000	800/900/1000
28U	1415	600/800/1000	800/900/1000
33U	1637	600/800/1000	800/900/1000
37U	1815	600/800/1000	800/900/1000
42U	2037	600/800/1000	800/900/1000

ORDERING INFORMATION

PRODUCT NUMBER	Capacity / Height	Width	Depth	Door Type
LM-FS	15 = 15U 18 = 18U 24 = 24U 28 = 28U 33 = 33U 37 = 37U 42 = 42U	6 = 600mm 8 = 800mm 10 = 1000mm	8 = 800mm 9 = 900mm 10 = 1000mm 12 = 1200mm	PS = Perspex Door PF = Perforated Door TG = Tempered Glass