

# LUMIFIBER FIBER OPTIC SOLUTION



## END STOP MICRODUCT CONNECTOR

### General Description

Used to seal off an open microduct. Easy installation without the needs of any specialize tools. Transparent cap for ease of monitoring of internal conditon.

### Material

	<b>Body</b>	Polycarbonate
	<b>Washer</b>	Polyacetal
	<b>Collar</b>	Polyacetal
	<b>Seal</b>	NBR
	<b>Lock Claws</b>	Stainless Steel
	<b>Sleeve</b>	Polyacetal

### Mechanical characteristics

<b>Temperature resistance</b>	-20°C – 50°C
<b>Pressure Resistance</b>	>25bar
<b>IP Rating</b>	IP68
<b>FR Resistance</b>	Yes
<b>Standard</b>	EN50411

### Ordering Information

Specification	Duct outer diameter (O.D) mm
Endstop connector EST3	3
Endstop connector EST4	4
Endstop connector EST5	5
Endstop connector EST6	6
Endstop connector EST7	7
Endstop connector EST8	8
Endstop connector EST8.5	8.5
Endstop connector EST10	10
Endstop connector EST12	12
Endstop connector EST12.7	12.7
Endstop connector EST14	14
Endstop connector EST16	16
Endstop connector EST18	18
Endstop connector EST20	20
Endstop connector EST22	22